



SUNFIRE MODEL 150 SPECIFICATIONS



SPECIFICATIONS

BTU/hour High Setting: 150,000 (44kW)
BTU/hour Low Setting: 130,000 (38kW)

Flow Rate on High: 1.10 GPH
Flow Rate on Low: .97 GPH

Run Time on High: Approx. 17 Hrs.
Run Time on low: Approx. 19 Hrs.

Fuels: Diesel, #2 fuel oil

Dimensions: 29"L x 36"W x 41"H
(73.7cm x 91.44cm x 104.1cm)

Fuel Tank Capacity: 19 Gallons (72L)

Weight with Empty Tank: 195 lbs. (88kg)
Weight with Full Tank: 320 lbs. (145kg)

Electrical Requirements: 120V 2A 60HZ or 12V Pure Sine Power Inverter (800W Minimum)

UL Listed: Yes

Where Manufactured: USA

IMPORTANT SAFETY INFORMATION

Minimum Clearance to Combustible Surfaces:
Front: 72" Right Side: 36"
Back: N/A Left Side: 36"

**Not for use in household residence.
Proper ventilation is required during operation.**

California Prop 65

This product can expose you to ceramic fibers, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.